



ID (Nominal)	ID (Actual)	OD	WT	JT	RD	GD	AS	GW	H
825	832	1066.6	114.3	88.9	926.3	939.8	3.2	8.3	44.5
900	914	1155.2	120.6	88.9	1002.5	1016.0	3.2	8.3	44.5
975	991	1245.0	127.0	88.9	1078.7	1092.2	3.2	8.3	44.5
1050	1067	1333.7	133.3	107.9	1172.7	1190.9	3.7	11.3	63.5
1200	1220	1512.0	146.0	107.9	1325.1	1343.3	3.7	11.3	63.5
1350	1372	1689.4	158.7	107.9	1470.1	1488.3	3.7	11.3	63.5
1500	1524	1866.8	171.4	120.6	1635.2	1653.4	3.7	11.3	63.5
1650	1676	2044.2	184.1	127.0	1800.3	1818.5	3.7	11.3	63.5
1800	1829	2222.6	196.8	127.0	1959.8	1978.0	3.7	11.3	63.5
1950	1981	2362.0	190.5	127.0	2123.7	2145.5	4.4	13.3	69.8
2100	2134	2540.4	203.2	127.0	2288.8	2310.6	4.4	13.3	69.8
2250	2286	2717.8	215.9	127.0	2453.9	2475.7	4.4	13.3	69.8
2400	2438	2895.6	228.6	127.0	2619.0	2640.8	4.4	13.3	69.8
2550	2591	3073.4	241.3	127.0	2783.8	2805.9	4.4	13.3	69.8
2700	2743	3251.8	254.0	127.0	2949.2	2971.0	4.4	13.3	69.8
3000	3048	3606.8	279.4	152.4	3247.7	3269.5	4.4	13.3	69.8
3600	3658	4356.0	349.0	152.4	3895.4	3917.2	3.7	12.7	50.8

Pipe Joint Detail 825-3600mm

Notes

1. Pre-lubricated rubber gaskets to be used with this pipe joint design.
2. See page 18 for pipe jointing procedure.
3. All dimensions are in millimeters unless otherwise shown.

